MITIGATING DROUGHT CONDITIONS THROUGH OPTIMIZING AQUIFER STORAGE AND RECOVERY (ASR) WELL OPERATION



WESTCAS 2016 Annual Conference

Nathan Nutter, P.E. Carollo Engineers


October 26, 2016




The Next Gold Rush




Arizona




New Mexico



South (Texas)



California



East






Figure 7. A 45-year ground-water hydrograph for confined-aquifer observation well CA Gd 6 near Solomons in Calvert County, Maryland, showing the declining water levels due to ground-water pumpage. Note the significant increase in rate of decline in the mid-1980s.


Northwest




Hawaii



ASR Operational Concept



ASR Operational Concept




ASR Strategies

 Mitigate/Sustain Declining Water Levels







ASR Strategies

- Mitigate/Sustain Declining Water Levels
- Increase Well Capacity
- System Redundancy and Flexibility - Potable Delivery
- Long-Term Storage for Drought
- Potential for Base Loading Water Treatment Plant Flows





etallicTemplateWithLogo.pptx

ASR Preliminary Steps

- Identify the funding source.
 - Drilling \$1,000,000
 - Equipping Construction -\$2,250,000
 - Engineering and Construction Management - \$750,000
 - Total Cost \$4,000,000




- Conduct geochemical analysis between groundwater and source water (core sample needed).
 - Is additional treatment required at the plant?
 - Are the pH differences small enough to mitigate mobilization of adverse constituents and/or mineral deposition?
 - (In some states) Is the recharged water of a lesser quality than the groundwater?
 - Will TTHM's be an issue? Is a dechlorination system required?
- Verify whether lateral velocity is an issue
- Identify potential ASR well sites

Goals for Optimizing an ASR System:

- Minimize clogging within the well
 - Particulate clogging
 - Air entrainment
 - Biofouling







Effects of Clogging




- Reduced injection/recovery rates
- Increased O&M Cost
 - Capital costs
 - Energy costs
 - Labor costs







-650'- Static Water Level -838'- Top of Screen



-650'- Static Water Level -838'- Top of Screen




-650'- Static Water Level -838'- Top of Screen




-650'- Static Water Level -838'- Top of Screen

Injection Issues:

Air entrainment



Reverse Siphon Concept and Bowl Assembly Hydraulics



Goals for Optimizing an ASR System:

- Minimize clogging within the well
 - Particulates
 - Air entrainment
 - Biofouling
- Identify ratio of recharge/recovery that is acceptable
 - Well redevelopment
 - Data acquisition




ASR Redevelopment Benefits:

- Condition aquifer for injection operations
 - Reduce clogging potential
- Improve injection and recovery rates
 - Extend life-cycle of the well
- Use permanent pump equipment
 - Eliminate pulling the pump assembly
 - Reduce maintenance costs and time






Data Acquisition for Determining Efficiency



Data Acquisition for Determining Efficiency



SEPT 2011

Recharge and Recovery Cycles

Summary of Redevelopment

- Operator friendly
- Efficient cleaning method (in-situ equipment)
- Removal of "big" air and fine grained particulates
- Verify recharge/recovery ratio
- Maximize recharge efficiency through backwash program





Goals for Optimizing an ASR System:

- Minimize clogging within the well
 - Particulates
 - Air entrainment
 - Biofouling
- Identify ratio of recharge/recovery that is acceptable
 - Well redevelopment
 - Data acquisition
- Multi-level institutional involvement
 - Operators
 - Engineers
 - Management







Q&A and Discussion

Nathan Nutter, P.E.
Carollo Engineers
4600 E. Washington St, Ste 500
Phoenix, AZ 85034
602-474-4182
nnutter@carollo.com